

# BLUE LINER

High-quality brown testliner made of 100% recycled fibres.  
Presents and protects the final product with the best optical effect.

Grade Description	Nominal grammage g/m <sup>2</sup>	Burst strength kPa	SCT cd kN/m
Test method	ISO 536	ISO 2759	ISO 9895
Tolerance	+/- 3%	Guaranteed/Typical	Guaranteed/Typical
Blue Liner 90 g/m <sup>2</sup>	90	188 / 209	1.39 / 1.54
Blue Liner 100 g/m <sup>2</sup>	100	218 / 242	1.58 / 1.76
Blue Liner 110 g/m <sup>2</sup>	110	238 / 264	1.68 / 1.87
Blue Liner 120 g/m <sup>2</sup>	120	257 / 286	1.88 / 2.09
Blue Liner 125 g/m <sup>2</sup>	125	267 / 297	1.98 / 2.20

Cobb 60 g/m<sup>2</sup> (ISO 535) Max 60 Typical 35

Moisture content : 8,0 +/- 0,5% (ISO 287)  
Test conditions : 23°- 50% RH (ISO 187)

Valid: from May 2024



Blue Paper SAS  
4, rue Charles Friedel  
CS 30009  
F - 67017 Strasbourg Cedex

✉ sales@bluepaper.eu  
🌐 www.bluepaper.eu  
☎ +33 3 88 41 75 32  
🖨 +33 3 88 41 75 98